

**NitroGen**

Distribuido en España por:



N<sub>2</sub>  
A

## NG CASTORE PRO

### Membrane Nitrogen generator electronic controlled

The NitroGen series CASTORE PRO are Membrane Nitrogen Generators. They are engineered to transform standard compressed air into a safe, regulated supply of Nitrogen with a purity up to 99.5%. An optional channel can provide up to 45 L/min of compressed, dry and regulated air.

The exclusive electronic flow control allows to generate Nitrogen with a higher purity using a smaller volume of air which results in reduced energy costs and maintenance of any external compressor. Continuous control of the operating parameters allows to maintain the system at its maximum efficiency.

The CASTORE PRO with its dual Nitrogen and Air outlets has been developed to meet specific requirements in term of gas, flow, purity and pressure in LC-MS applications. It can be used for the evaporation of solvents in samples being analysed.

#### Main applications

- LCMS
- Solvent evaporation

#### Main advantages

- ✓ Compatible with all LCMS
- ✓ Dual Nitrogen and Air generator
- ✓ Low noise
- ✓ Low maintenance
- ✓ Generates nitrogen on demand
- ✓ Exclusive electronic flow control
- ✓ Designed to run 24 hours a day



**R Evolution**  
in Gas Generators

## Specifications



Models: NG CASTORE PRO	25	25-40	45	45-40	60
<b>N2 outlet</b>					
Flow rate (Max)	25 l/min		45 l/min		60l/min
Outlet pressure (min; Max)	2.0 bars; Inlet pressure – 1.0 bar				
Nitrogen purity (Inlet Pressure > 8 bar)	> 98.5 % @ 25 l/min > 99.5 % @ 10 l/min		> 98.5 % @ 45 l/min > 99.5 % @ 25 l/min		> 98.5 % @ 60 l/min
<b>Dry Air outlet</b>					
Flow rate (Max)	-	40 l/min	-	40 l/min	-
Outlet pressure	-	Inlet press. - 1bar	-	Inlet press. - 1bar	-
Dew point	-	< -20°C (-4°F)	-	< -20°C (-4°F)	-
<b>Air inlet</b>					
Air inlet requirement	Particulate: <1 micron Dewpoint: < 20°C (68°F) Oil: <0.01 mg/m <sup>3</sup>				
Flow rate (Max)	115 l/min	155 l/min	135 l/min	175 l/min	150 l/min
Supply pressure (min; Max)	5 bars; 10bars				
Temperature (min; Max)	1°C (34°F); 45°C(113°F)				
<b>Communication</b>					
LCD with touch screen	Standard				
RS485	Standard				
RS232	For service				
<b>General data</b>					
Supply rating	100-240Vac 50/60Hz – 1A				
Connection type	IEC320-C13				
Installation power (max)	25W (30VA)				
Fuse rating	2 x 1A -240Vac (5x20mm)				
Net weight	<30 kg		<35 kg		
Dimensions (W x D x H) mm	260 x 280 x 1200				
<b>Connections</b>					
N2 outlet port	¼" BSPP female				
Dry Air outlet port	¼" BSPP female				
Inlet port	¼" BSPP female				
Drain port	¼" BSPP female				
<b>Operating/storage conditions</b>					
Temperature	5-35°C (41-95°F)				
Humidity (max, non condensing)	80% at 25°C (77°F)				
Noise	<25dB(A)				
IP rating	IP20				
Pollution degree rating	2 (with no aromatic compounds)				
Altitude	< 2000m				

### Ordering codes

#### Gas Generators

6920.50.025	CASTORE PRO 25
6920.50.125	CASTORE PRO 25-40
6920.50.045	CASTORE PRO 45
6920.50.145	CASTORE PRO 45-40
6920.50.060	CASTORE PRO 60
6920.50.160	CASTORE PRO 60-40

#### Accessories

6920.50.000	50 L Nitrogen tank with pressure regulator and safety valve
6920.50.005	Dual 25L Nitrogen + 25L Air Tank With pressure regulator and safety valve

#### Consumable

6930.00.140	Service Kit 8000H for CASTORE models
-------------	--------------------------------------



LNI GGI srl  
www.lni-swissgas.eu

