

ZA FID AIR C

Zero Air generator with integrated air compressor

The AirGen series **ZA FID-C Air** is able to remove the total hydrocarbons to less than 0.05 ppm. Very compact, the **ZA FID-C** is available with a low noise built-in pistons compressor, 100% oil-free.

The filtration of the hydrocarbons is performed using a catalytic oven filled with palladium. The reduction of hydrocarbons, including methane, and carbon monoxide decrease the background noise level and gives much better baseline stability, considerably increasing detector sensitivity and ensuring precise analytical results. High efficiency coalescing pre-filtration and post filtration of particulate size greater than 0.01 microns are used to prevent any kind of particles from entering the analytical device. The **ZA FID-C Air** has a very simple and efficient interface. It can also be managed by the HydroGen series HG PRO and HG BASIC and is ideal to supply Hydrocarbon free Air to FID detectors.

Main Applications

- GC-FID
- GC-NPD
- GC-FPD
- GC-PFPD
- THA
- Gas sensing

Main advantages

- ✓ Easy use and quick installation
- ✓ High flow rate up to 6 L/min
- ✓ Pressure up to 7 bar
- ✓ RS 485 and RS232 as standard
- ✓ Purity: < 0.05 ppm THC
- ✓ Dew-point < -30°C
- ✓ Reduced foot print
- ✓ Stackable with HG BASIC and HG PRO





Specifications

Models: ZA FID AIR C	1.5	3.0	6.0
Zero Air outlet			
Flow-rate (max)	1.5 l/min	3.0 l/min	6.0 l/min
Outlet pressure (min)	2 bars (29 psi)		
Outlet pressure (max)	7 bars (100 psi)		
Total hydrocarbon content	< 0.05ppm		
Dew-point	< -30°C		
Communication			
RS485	Standard		
RS232	Standard		
General data			
Supply voltage	110 or 230Vac 50/60Hz		
Connection type	IEC320-C13		
Rated power (max)	750W		
Fuse rating (5x20mm)	4A		
Dimensions	27(W) x 41(H) x 44(D)cm		
Net weight	35 kg		
Noise	58dB(A) @ 1,5 m from front		
Connections			
Outlet port	1/8" female BSPP		
Water drain port	1/8" female BSPP		
Operating conditions			
Temperature	5-35°C (41-95°F)		
Humidity (max, non condensing)	80% at 25°C (77°F)		
IP rating	IP20		

Ordering codes

Gas Generators

6920.25.115

6920.25.130

6920.25.160

Consumable

6930.00.180

ZA FID AIR C 1.5

ZA FID AIR C 3.0

ZA FID AIR C 6.0

Filter elements for ZA FID AIR C

LNI Swissgas

www.lni-swissgas.eu

